

## Pro-Ject 2 **X**perience Comfort

Manual turntable with electronic speed change, automatic cut-off and fitted cartridge Ortofon 2M Red, Sumiko Blue Point No. 2 or Ortofon MC Rondo Red



### Turntable

- Available finishes

Cherry



Apple




Olive



Wenge



Black gloss



- A quiet running AC motor with a two-step acryl pulley drives the platter's outside edge via a belt.
- The medium density fibre plinth stands on three height-adjustable Sorbothane®-damped aluminium cones.
- The motor is decoupled from the plinth to reduce vibration transmission.
- The resonance-optimised platter is a sandwich construction utilising the hub, a fine-balanced medium density fibre platter weighing 2Kg, a 4mm thick flat-ground layer of vinyl and a screw-down metal record clamp.
- The platter's low-tolerance chrome-plated stainless-steel axle runs on a Teflon bearing plate in a sintered bronze bearing housing.
- Electronic speed change for 33/45 r.p.m.
- An opto-electronic switch stops the motor as soon as the cartridge has reached the run-out groove.
- Connection to the phono input of the amplifier can be made with connecting cables of your taste through the gold plated phono sockets and earth screw. A standard cable is provided.
- External power supply avoids potential electro-mechanical interference.

### Tonearm Pro-Ject 9c

- The turntable is supplied with MM-cartridge Ortofon 2M Red, Sumiko Blue Point No. 2 high output MC-cartridge or with Ortofon MC Rondo Red low output MC-cartridge cartridge fitted.
- Conical carbon-fibre armtube avoids standing wave reflections.
- Low mass aluminium headshell securely glued to armtube.
- The inverted bearings consist of four hardened stainless steel points bearing in sapphire cushions.
- Flexible counterweight shaft avoids vibration at undesirable frequencies.
- Solid armbase permits accurate height adjustment of armtube and VTA (vertical tracing angle).
- Single-screw fixing of armtube allows rotation for easy adjustment of needle azimuth despite fixed headshell.
- The straight armtube with an effective length of 9" reduces toe-in error.
- Silicone-damped armlift can be adjusted to suit working height of the arm.
- The internal wiring consists of flexible high-purity copper from the headshell right through to the gold-plated phono sockets.

Dimensions W x H x D: With dust cover closed 460 x 160 x 360mm, dust cover open 460 x 417 x 460mm.

**Ortofon 2M Red:** Output voltage 5,5mV. Recommended load resistance 47kohms (MM-input).

**Sumiko Blue Point No.2:** Output voltage 2,5mV. Recommended load resistance 47kohms (MM-input).

**Ortofon MC Rondo Red:** Output voltage 0,5mV. Recommended load resistance 10 – 200 ohms (MC-input).

The manufacturer reserves the right to alter the technical specifications without notice.  
The colours in the picture may differ slightly from the actual article due to inaccuracies in the printing process.