Let us entertain you











Like all other Jamo Custom products, this in-ceiling speaker features a 2-position impedance switch and a 3-position tweeter level adjustment to match your musical preferences and system requirements. The premier IC 610 FG features a 3-position midrange-level adjustment and an impressive 4-way construction with a 254mm/10in woofer, 38mm/1½in silk dome midrange units and two highly efficient tweeters.

The speaker's plastic 'bridge' make installation very easy as you can safely use this as a handle leaving your other hand free for holding a drill, screwdriver etc. The speaker is a one-piece item which means that you only needs to make one visit to the customer to mount it.
The grille covers the whole of the speaker which makes painting the product both simpler and quicker as you don't need to paint the speaker itself.

For more information visit www.jamo.com

Specifications	**IC 610 FG**
System	4-way in-ceiling
Woofer (mm / in)	254 / 10
Midrange (mm / in)	38 / 1½
Tweeter (mm / in)	19 / ¾ + 25 / 1 DTT
Power (W long / short term)	100 / 200
Frequency Range (Hz)	32 - 22,000
Impedance (Ohm)	4 - 8 switchable
Hole dimension HxWxD (mm / in)	Ø310 x 157 / Ø12.2 x 6.2
Dimensions HxWxD (mm / in)	Ø342 x 172 / Ø13.5 x 6.8
Back box size (Litre/in3)	26 / 1590
Weight (kg / lb)	3.5 / 7.7
Finish	White (paintable)



Soundwise, IC 610 FG is comparable with C 605 and C 603

Jamo®
Danish Sound Design

16.08.2011